



Merrychef Advanced High Speed Cook Oven

©ikon° e3 HP



Standard Features


- Oven cavity to suit up to 297mm x 321mm / 11" x 12.7" tray size
- 2 rack positions
- Up to 5 times faster than a convection oven
- Advanced Cooking Technology® combines two heat technologies: microwave and convection heat
- · Ventless cooking capabilities through built in catalytic converter
- Colour easyTouch® icon driven touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power setting and user instructions for each stage
- 3 cooking levels for power saving yet faster cooking and baking
- Quick preheat function
- Includes turntable for even browning
- Easy menu updates or data transfer via USB
- MenuConnect^M ethernet connection for remote menu updating and diagnostics
- Precise temperature setting range from 100°C 275°C
- · Self-diagnostics capability to monitor components
- · Cool to touch door exterior
- Stainless steel construction
- Easy to clean interior
- Easy access to front facing air filter
- Multi-languages available

ncludes

- Cast turntable tray coated (3)
- Handle
- Turntable disk
- Cool down pan
- · Cleaning care package, consisting of:
 - 1x oven cleaner (bottle)
 - 1x oven protector (bottle)

Accessories

- Circular Teflon liners
- Trays
- Disk
- Racks
- Handles




Airflow (side view)


Air in the oven cavity is cleaned by being drawn through the catalytic converter* (1) by the convection fan (2) and then passes over the heating element and is circulated into the oven cavity (3) at the set temperature.



Merrychef Advanced High Speed Cook Oven

cikon e3 HP





ELECTRICAL SUPPLY

400-415V, 50Hz (2P+N+E) Rated power consumption Rated current

20A 5 pin plug

All Merrychef ovens require installing a type D circuit breaker for all installations.

POWER OUTPUT (APPROX.)

Microwave Convected heat 3 kW Combination mode

**This is approximate microwave power output.

MOFFR

Australia moffat.com.au

New Zealand moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au

Queensland Ph 07-3630 8600 qldsales@moffat.com.au

Western Australia Ph 08-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

4.7 kW

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd



MICROWAVE POWER

Microwave settings, off or 5-100% in 1% increments Distribution system, rotating active antennae

CONVECTED HEAT

Temperature settings off and from 100°C to 275°C in 1°C steps

Distribution system, tuned impingement

DIMENSIONS

Width 590 mm Depth 559 mm 551 mm Heiaht 62.5 kg Weight

PACKED DIMENSIONS

Width 770 mm Depth 860 mm 760 mm Weight (including cleaning system) 71 kg **INSTALLATION REQUIREMENTS**

Rear 50 mm Right 50 mm Left 50 mm

INSTALLATION REQUIREMENTS

For precise installation instructions please refer to the units installation manual



