


# specifications

## BME600-A Series

ActiveCore Series, 1 Door (Glass), Upright Fridge

Project: \_\_\_\_\_

Item No: \_\_\_\_\_



CABINET	
Model ID	BME600N-A   BME600N-AC
SKOPE ID	SM60GYN   SM60BYN
Doors	1 × self-closing, reversible, double glazed, single Low-E, lockable, argon filled, toughened safety glass swing door (hinged RH)
Internal door opening	1 × door openings: 1454mm high × 620mm wide
Shelves	4 × wire and 1 × stainless steel   5 × wire and 1 × stainless steel
	Wire shelves: Adjustable height, 625mm wide × 520mm deep Stainless steel bottom shelf: Not adjustable, 625mm wide × 515mm deep
Sign	n.a.   Illuminated sign
Material	Powdercoat galvanized steel
PERFORMANCE	
Max. ambient temp.	43°C
Temperature range	1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C)
ELECTRICAL	
Climate class	5 (40°C/40% RH)
Interior side lighting	1 × 1370mm, 15W LED   1 × 1370mm, 15W LED
Interior shelf lighting	n.a.   n.a.
Sign lighting	n.a.   1 × 670mm, 7W LED
Power cord	Supplied with 2.0m, 10 Amp plug and lead
Power supply	220-240 Volts a.c. 50 Hz, single phase supply
Current draw	2.9 Amps (includes unit 2.6 Amps)
REFRIGERATION	
Controller	SCS Connect (SKOPE-connect™ compatible)
Connectivity interface	Bluetooth® wireless technology
Refrigeration system	Bottom mounted, integral, removable ActiveCore refrigeration unit (UBHCNI-0008)
Refrigerant	R290 / 99g (natural refrigerant)
Nominal capacity	740 Watts
Heat rejection (Avg/peak)	95 Watts/125 Watts
Drainage	No plumbing required

DIMENSIONS		
Height	External 2005mm* / 2195mm**	Internal 1454mm
Width	740mm	640mm
Depth	795mm	602mm
Floor area	0.63m <sup>2</sup>	
Weight	185kg	
Volume	584 litres	

\* Height 2005mm without sign (BME600-A)  
\*\* Height 2195mm with sign (BME600-AC)  
\*\*\* Depth 745mm excludes removable door handle, door lock bracket and rear stand-off

Dimensional tolerances		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5mm	
More than 1 metre	-5mm to +10mm	
Length of multiple cabinets		
	At each joint	At each end wall
Less than 1 metre	±5mm	+15mm
More than 1 metre	-5mm to +10mm	+15mm

Ventilation requirements	
Top	50mm
Sides	Not required
Back	50mm
Bottom	50mm

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2018 SKOPE Industries Limited

PSS0520 Rev. 2.2 Oct. 2019

**SKOPE INDUSTRIES LIMITED**

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: skope@skope.com, Website: www.skope.com

